

Mobile Computer

TC603

Thinner, Lighter, and Ingeniously Constructed For a More Powerful Enterprise Mobile Companion



Qualcomm CPU SDM 660 2.2GHz Octa Core



Operating System

Android 10



Drop Spec. 1.6m



Sealing Standard

IP65



Memory 4GB/64GB



Scan Engine



Honeywell N4603



Weight 235g



Replaceable Battery

4000mAh



Warehouse





Logistics

Field Service





TC603 Specification

Update Date: 2021. 12.07

Physical Characteristics		
Dimensions	159.4mm L x 78.4mm W x 14.2mm (main body) / 24.62mm (scanner) H	
Weight	235g (with battery)	
Display and Panel	 5.99", 18:9 Full-HD+ 1080 x 2160 (450nit) Capacitive 5 points multi-touch panel Gorilla® Glass 5 	
Expansion Slots	One user accessible micro SD Memory slot with SDHC compliance and software image upgrade features Two user accessible Nano SIM slots USB 3.1 (type-C) support USB OTG Support DC in 5V/2A Cradle connector (two pogo pin) DC power input	
Keys and Buttons	 Front key: 3 touch soft keys Side key: Scan key left and right, volume key up and down, power key and one function key (programmable) 	
Indicators	One 3-color (green/red/blue) LED RED LED Battery Charging Twinkling to indicate battery low status(less than 15%) Green LED Battery Fully charged Blue LED Message notice Others All of LEDs can be controlled by software API No LED (Red and Green) display when battery is out(even AC IN)	
Audio and Voice	 One speaker (95±3dB @ 10cm) One receiver and dual noise-cancelling microphones Type-C USB adaptor for 3.5mm DIA stereo headset jack 	

Performance Characteristics		
Operating System	Android 10 with GMS	
CPU	Qualcomm® Snapdragon™ 6602.2GHz Octa Core	
Memory	eMCP 4GB LPDDR4x + 64GB eMMC 5.1	
User Environment		
Operating Temp.	-20~50℃	
Storage Temp.	-30~70°C (without battery)	
Charging Temp.	0~45℃	
Humidity	10%~90% (non-condensing)	

User Environment	
Operating Temp.	-20~50°C
Storage Temp.	-30~70°C (without battery)
Charging Temp.	0~45℃
Humidity	10%~90% (non-condensing)
Sealing Standard	IP65
Drop Specification	1.6m
Tumble Specification	0.5m tumbles for 300 cycles and 600 drops
ESD	+/-7KV direct discharge, +/-15KV air discharge

Network Connection		
Wireless PAN	Bluetooth 5.0	
Wireless LAN	 802.11a/b/g/n/ac Wireless LAN, 2.4GHz and 5GHz Compliant with WEP, WPA and IEEE 802.11i WPA2, WPA3, Fast roaming. 	
Wireless WAN	 GSM: 850,900,1800,1900 MHz WCDMA: B1, B2, B5, B8 LTE: B1, B2, B3, B4, B5, B7, B8, B12, (B17), B19, B20, B28, B38, B39, B40, B41(100M only) 	
GPS	aGPS, GPS, GLONASS, Beidou, Galileo, QZSS, SBAS	

Data Capture		
Scan Engine	Honeywell N4603 (2D scan engine)	
Camera	 Front camera: 5M pixel CMOS color camera Rear camera: 16M pixels CMOS color camera with autofocus LED flash light with torch 	
NFC	I ISO14443-4 (Type A, Type B), ISO15693Mifare, Felica(ISO/IEC18092)	
Sensor		
Sensor	Accelerometer, Gyroscope, e-Compass, Light Sensor, Proximity Sensor	
Power		
Battery	Main battery : 3.85V, 4000mAh Li-polymer smart battery pack	
Power Adapter	100~240Vac, 50/60Hz Input9V/2A 18W output(TBC)	
Regulatory Compliance		
Certifications	CE, NCC, FCCRoHS, REACH, WEEE	

Accessories

Accessories

- Adapter
- USB Charging Cable (Type C)
- Protective Boot (Optional)
- · Hand Strap with Protective Boot(Optional)
- Spare Battery(Optional)
- Pistol Grip(Optional)
- · Cradle (1 Terminal + 1 External Battery) (Optional)