

Mobile Computer

MC432

Superior Application Flexibility for Diverse Industries



Qualcomm Snapdragon

660 2.2GHz Octa Core



Operating System

Android 10



Drop Spec.

1.6m



Sealing

IP65



Weight

323g (with battery)



Replaceable Battery

4000mAh



Warehouse





Manufacturing







MC432 Specification

Update Date: 2021. 04.13

Physical Characteristics					
Dimensions	181.55mm *77mm *33.77mm				
Weight	323g (with battery)				
Display and Panel	 4.3", WVGA 480x800 IPS panel Gorilla® Glass Multi-touch projected capacitive; fingertip (bare or gloved) input Wet finger, Glove 				
Expansion Slots	 One user accessible Nano SIM slots(only for LTE version) One micro SD memory slot with SDXC compliance. IO: Type C (support display output), 2 Pogo Pins 				
Keys and Buttons	 1-screen keypad, Physical keypad type (23 keys) with white color backlight Side key: Scan key left and right, power key, volume key 				
Indicators	 One vibrator for ring in indication Audio tone indication LED behavior Charging LED Charging: Red Fully charged: Green Scan LED Scanning: Red Scan successfully: Green (Blinking once) 				
Audio and Voice	One speaker (95dB @ 10cm) One receiver and dual microphone Support echo cancellation and noise suppression				

• 3.5mm DIA stereo headset jack

Performance Characteristics				
Operating System	Android 10GMS for LTE version			
СРИ	Qualcomm® Snapdragon™ 660 2.2GHz Octa Core			
Memory	 3GB RAM+32GB Flash ROM(Standard) 4GB RAM+64GB Flash ROM(Optional)			
User Environment				
Operating Temp.	-20~50℃			
Storage Temp	40-70°C (without batton)			

User Environment				
Operating Temp.	-20~50℃			
Storage Temp.	-40~ 70 °C (without battery)			
Charging Temp.	0~45℃			
Humidity	5%~95% non-condensing			
Sealing	IP65 Standard			
Drop Specification	1.6m			
Tumble Specification	0.5m tumbles for 300 cycles and 600 drops			
ESD	+/-8KV direct discharge, +/-15KV air discharge			

Network Connection				
Wireless PAN	Bluetooth 5.0			
Wireless LAN	802.11a/b/g/n/ac Wireless LANIEEE 802.11 d/h/i/r			
Wireless WAN (Only for LTE Version)	 GSM: 850,900,1800,1900 MHz WCDMA: B1, B2, B5, B8 LTE: B1, B2, B3, B4, B5, B7, B8, B12, (B17), B20, B28A, B28B, B38, B39, B40, B41 			
GPS	GPS, GLONASS, Beidou			

Data Capture	
Scanner	 Support 1D/2D Honeywell N3601, Honeywell N6703, Datalogic H2 Scanning Angle: 30°
Camera	Rear camera : 16M pixels CMOS color camera with autofocus LED flash light
NFC	ISO14443-4 (Type A, Type B), ISO15693Mifare, Felica(ISO/IEC18092)
Sensor	
Sensor	Accelerometer, Gyroscope, e-Compass, Light Sensor, Proximity Sensor
Power	
Battery	Standard Battery: 3.85V, 4000mAHOne backup battery for battery swap
Power Adapter	 100~240Vac, 50/60Hz Input 5V/3A 15W, 9V/2A 18W output(QC3.0)
Regulatory Co	mpliance
Certifications	CE(RED), FCC, NCC, IC, SRRCCB, IEC62368(Battery pack),UN38.3

ı.or	サリナリハ	atio	ne	

- · RoHS, REACH, WEEE
- Energy-03

Accessories

Accessories

- Adapter
- · Charging Cable(Type C)
- Hand Strap
- · LCM protector
- Cradle (1 Terminal + 1 External Battery) (Optional)
- Rubber Boot(Optional)

